

Hand-Held Metal Detectors Comparisons

Hand-Held Metal Detectors Guide/Super Scanner/ Superwand/THD

Features and Specifications	THD	SSV	SW	Guide
7 selectable sensitivity levels for precise calibration to threats.				✓
USB-C rechargeable lithium ion battery to enhance product endurance and reduce waste.				✓
EMI Offset button to eliminate electromagnetic interference (EMI).				✓
Single or multi-unit modular charging base system to improve charging and storage efficiency.				✓
4-level charge indication for accurate comprehension of remaining charge.				✓
Weatherproof, dimpled, microtexture rubber grip for superior traction while screening in adverse environmental conditions.				✓
Heartbeat charging indicator to show charge progress while mounted to charging base.				✓
IP 65 Waterproof.				✓
Durable. Exceeds Mil-Std-810F (drop test) Method 516.5, procedures II and IV.		✓	✓	✓
8in (20.3cm) or more scan surface for rapid screening.		✓	✓	✓
Audio Alarm mode.		✓	✓	✓
Reduced sensitivity switch to eliminate rebar interference.		✓		✓
IP 66 Waterproof.	✓			
Integrated LED Flashlight.	✓			
360° detection area.	✓		✓	
Accurate detection of all ferrous, nonferrous and stainless steel weapons, contraband and other metallic objects.	✓	✓	✓	✓
Low-profile vibration and visual LED alarm mode.	✓	✓	✓	✓
Ultra sensitive response to metal objects.	✓	✓	✓	✓
Self-calibrating. Does not require ongoing adjustments.	✓	✓	✓	✓
3 Year Limited Parts/Labor Warranty.	✓	✓	✓	✓



Todd Research Limited
 9C Trafalgar Way | Bar Hill | Cambridgeshire
 | CB23 8SQ | UK tel: +44 1480 832202
 email: xray@toddresearch.co.uk
 web: www.toddresearch.co.uk

Design | Manufacture | Installation | Training | Service

Guide

Product Specification

Dimensions

Width 3.375" (9 cm)
Thickness 1.125" (3 cm)
Length 16" (41 cm)
Total Weight 1 lb (0.5 kg)

Indicators

- Audible Speakers
- LED Alert Lights
- Green: Power On
- Amber: Battery Low
- Red: Alarm Condition

Controls

- Power Switch (Selectable Vibrating Alarm)
- Interference Elimination Switch
- Adjustable sensitivity

Operating Temperatures

- -4° F (-20° C) to 140° F (60° C)

Environmental

- IP 65 rating

Audio Frequency

- 2 kHz

Tuning

- Automatic

Battery

- Lithium Ion 3.8V 2.5 Ahr (included)
- Capacity 125 hrs
- Optional charging base



Super Scanner V

Product Specification

Dimensions

(Super Scanner V): (mm)
420 (L) 83 (W) 41 (H)
Weight 500 g

Indicators

- Audible Speakers
- LED Alert Lights
- Green: Power On
- Amber: Battery Low
- Red: Alarm Condition

Controls

- Power Switch (Super Scanner V) (Selectable Vibrating Alarm)
- Interference Elimination Switch

Operating Temperatures

- -35° F (- 37° C) to 158° F (70° C)

Humidity

- To 95% non-condensing

Audio Frequency

- 2 kHz

Tuning

- Automatic

Battery

- Super Scanner V - 9V battery
- No tools required to change battery
- Optional rechargeable battery kit



SuperWand

Product Specification

Dimensions

(SuperWand): (mm)
483 (L) 83 (W) 32 (H)
Weight 527 g

Indicators

- Audible Speakers
- LED Alert Lights
- Green: Power On
- Amber: Battery Low
- Red: Alarm Condition
- Silent/Vibrate (TRSW only)

Controls

- Power Switch (SuperWand)
- 3-way switch (On, Off, Silent)
- Interference Elimination Switch

Operating Temperatures

- -35° F (- 37° C) to 158° F (70° C)

Humidity

- To 95% non-condensing

Audio Frequency

- 2 kHz

Tuning

- Automatic

Battery

- Super Wand - 9V battery



THD

Product Specification

Dimensions

Length 8.43" (22cm)
Width 3.25" (8.3 cm)
Thickness 1.625" (4.1 cm) tapered to 1.125" (2.9 cm)
Weight 6.4 oz (.2 kg)

•LED Alert Lights

- Green: Power On
- Amber: Battery Low
- Red: Alarm
- Silent/Vibrate

Operating Temperatures

- -35° F (- 37° C) to 158° F (70° C)

U.S. Patent No. D497,559 S

Audio Frequency

- 2 kHz

Tuning

- Automatic

Battery

- Requires one 9V battery (included)



 **BUY NOW**




SCAN ME!



Law Enforcement
Government
Buildings



Embassies &
Consulates
VIP Residences



Hotel Complexes
Shopping Centres



Schools &
Universities



Public Event Venues
& Stadiums